

Quick Slip™

Description: QUICK SLIP is a Special Proprietary Blend of Products, Dark Brownish Color Designed to Effectively Reduce HTHP. It Is Universally Compatible With Oil Based, Synthetic And Water Based Fluid. QUICK SLIP is a Patent Pending Cellulosic Base Formulation.

Benefits and Use:

- Effectively Reduces And Controls API Filtration At Temperatures > 425° F
- Provides Superb HT/HP Control.
- Provides Lubricity For High Angle And Horizontal Drilling Applications

Additional Advantages:

- Compatible With Most Drilling, Completion And Workover Fluids
- Completely Inert In the Fluid.
- Thermally Stable To >425° F.
- Promotes Fluid Stability
- Biodegradable and Non-Toxic.
- Storage For Long Periods Of Time, It Does Not Degrades
- Enhances Flow Properties
- Readily Dispersible In Pure Oil Systems
- Improves ROP
- Great Lubricity Properties

Physical Properties:

Form:	Dark Brownish Powder
Bulk Density:	1.3 (+/-)
pH (Water Solution 1%)	5.1

Lubricity:

- Minimizes Down hole Friction Forces
- Enhances Directional Drilling Operations
- Reduces Torque
- Optimizes Tripping Time



Formation

- Helps To Stabilize Shales Mechanically And Chemically
- Creates A Thin, Strong Wall Cake
- Provides Excellent Seepage Control

Recommended Treatment

- For Recycled Fluids 4 To 6 ppb.
- For New Fluids 6 To 10 ppb.
- For Spotting Fluids 22 To 26 ppb

Packaging:

50 Lb. multi-wall paper sacks. Material is palletized in 42x48 pallets and 40 bags per pallet